


# XCT25\_EV 汽车起重机 / Truck Crane

## 技术规格书


Technical specifications



25 t



44 m



52 m





2022年2月 第1版  
1<sup>ST</sup> edition, Feb 2022

# 目录

## Contents

<b>目录</b>	
<b>Contents</b>	
尺寸参数 Dimensions	4
技术规格 Technical specifications	5-8
车型与选装件 Version and optional equipment	9
重量/作业速度 Weight / Working speeds	10
臂架组合方案 Boom / Jib combinations	11
主臂 Boom	12-14
副臂 Jib	15-16
主要技术参数表 Table of main technical parameters	17-18
符号标识 Description of symbols	19
注意事项 Notes	20-21

# 尺寸参数 Dimensions



# 技术规格

## Technical specifications



### 底盘

**车架** 徐工设计、制造，全覆盖式走台板，防扭转箱型结构，高强度钢材制造。

**支腿** 4支腿；纵向H形布置，操作杆控制液压动作；可由底盘任一侧同时或单独控制各支腿的动作，设有水平仪；带第五支腿；且垂直支腿带有液压双向锁。  
支脚盘尺寸：φ400mm  
最大起重量时支腿反力：369KN

**发动机** SC7H270Q6，直列六缸水冷电控柴油发动机，上柴，额定功率199kW/2300rpm，最大扭矩1000Nm/1200~1700rpm，最大基准扭矩：1200N.m；国六排放标准。燃油箱容积：230L；尿素箱容积：35L。

**变速箱** 特百佳12档AMT变速箱

**车桥** 美驰高强度车桥，2,3桥驱动。

**悬挂** 前悬架：纵置钢板弹簧，筒式减震器；  
后悬架：橡胶悬架，重量轻，免维护。

**轮胎** 10个轮胎，1个备胎，前桥装单胎，中桥、后桥装双胎。  
轮胎规格：315/80R22.5

**电机** 特百佳 TZ365XSTPG03三相交流永磁同步电机  
额定扭矩：860N.m  
峰值扭矩：2150N.m  
额定功率：90kw  
峰值功率：180kw



### 底盘

**制动** 行车制动：双回路气压制动，作用于所有车轮。  
驻车制动：弹簧储能制动，作用于2-3轴车轮。  
辅助制动：发动机排气制动和缓速制动

**转向** 机械式转向机构，带有液压助力

**驾驶室** 全宽驾驶室，乘员3人；配置收放机、可调式座椅、简易卧铺、多功能方向盘、安全玻璃、3只雨刷器、电动后视镜、电动门窗升降器、杂物箱、空调

**电气系统** 直流24伏特，串联12伏特的电池组2个。  
发电机 28伏特-70安培。

**动力电池** 额定容量：228Ah  
额定能量：140.95kwh  
额定电压：618.24V  
充放电倍率：1C

额定容量：173Ah  
额定能量：90.2kwh  
额定电压：521.64V  
充放电倍率：1C

## 技术规格

### Technical specifications



#### 上车

<b>结构</b>	徐工设计、制造，高强度钢材制造。
<b>液压系统</b>	底盘发动机驱动变量柱塞泵，用于起升、变幅、伸缩。负载敏感式比例多路换向阀，带有抗冲击阀、防气蚀阀；风冷式液压油散热器；
<b>操纵方式</b>	液控先导操纵系统，由左右2个操纵手柄控制，由液压泵和比例阀进行液压先导式控制起重机的全部动作
<b>主起升机构</b>	液压控制调速，装有双折线绳槽卷筒，由液压马达通过行星齿轮减速器驱动，内置常闭式制动器并带有平衡阀；
<b>副起升机构</b>	液压控制调速，装有双折线绳槽卷筒，由液压马达通过行星齿轮减速器驱动，内置常闭式制动器并带有平衡阀；
<b>回转机构</b>	四点接触球式回转支承，由液压马达驱动行星齿轮回转机构减速器驱动，可连续回转360°；具有动力控制或自由回转的功能，可无级调速；回转杆设有鸣响开关；
<b>变幅机构</b>	单支双作用前置液压变幅油缸，带有平衡阀
<b>操纵室</b>	新型钢制操纵室，装有无视野死角的前景窗，安全玻璃，车窗装有遮阳板，推拉式车门，座椅靠背可倾斜定位，操纵杆安装在座椅两侧的扶手台上；带推拉踏板；前窗顶窗装有雨刮器；标配冷暖空调；
<b>安全装置</b>	液压平衡阀；液压溢流阀；液压双向锁；力矩限制器；三圈保护器，防止钢丝绳过放；臂头设置高度限位，防止钢丝绳过卷；三色报警灯；



#### 臂架系统

<b>主臂</b>	5节，“U”形截面的筒形焊接结构。双缸绳排伸缩机构 主臂长度：11.2m ~ 44m。
<b>臂端单滑轮</b>	单滑轮，安装在主臂顶端用于单股钢丝绳起重作业，起重性能与主臂起重性能一致，但最大起重量不超过3t
<b>固定副臂</b>	1节桁架式焊接结构，具有0°、15°、30°三种固定副臂安装角 固定副臂长度：9m

# 技术规格

## Technical specifications



### Chassis

<b>Frame</b>	Designed and manufactured by XCMG, it is made of high strength steel with fully covered walking surface and anti-torsion box-typed structure.
<b>Outriggers</b>	Four outriggers arranged in H-shape are hydraulically controlled by control levers. There is an outrigger control station located at each side of the chassis, and there is a level gauge on each control station. The outrigger movements can be simultaneously or separately controlled on either side of the chassis. The 5th jack is equipped. There is a double-way hydraulic valve fitted in each jack cylinder. Outrigger float dimension: $\phi 400$ mm. Reaction force of outrigger at max. lifting load: 369KN
<b>Engine</b>	SC7H270Q6, in-line, 6-cylinder, water cooled, electric control diesel engine, made by Shanghai Diesel Engine, with rated power of 199 kW/2300 rpm and max. torque of 1000 Nm/1200~1700 rpm. Max. engine reference torque: 1200 N.m; complying with China VI emission standard. Fuel tank capacity: 230 L; AdBlue tank capacity: 35 L.
<b>Transmission</b>	12-Speed AMT transmission made by Top Gear.
<b>Axles</b>	High strength axles made by Meritor, 2nd axle and 3rd axle for driving.
<b>Suspensions</b>	Front suspension: longitudinal leaf spring balanced suspension, with cylindrical shock absorber. Rear suspension: rubber suspension, light dead weight and maintenance-free.
<b>Tires</b>	10 tires and 1 spare tire. The front axle is equipped with single tire, the middle and rear axles are equipped with double-tire. Tire specifications: 315/80R22.5
<b>Motor</b>	Top Gear TZ365XSTPG03 Three-phase AC permanent magnet synchronous motor Rated torque: 860 N.m Peak torque: 2150 N.m Rated power: 90 kw Peak power: 180 kw





### Chassis

<b>Brakes</b>	Service brake: dual-circuit air pressure brake, acting on all wheels. Parking brake: spring-loaded brake, acting on the wheels of axles 2~3. Auxiliary brake: engine exhaust brake and engine retarder brake
<b>Steering</b>	Mechanically steering mechanism with a hydraulic booster.
<b>Driver's cab</b>	Full-dimension cab, three passengers are allowable. It is equipped with a radio player, adjustable seats, a simple bunk, a multi-function steering wheel, safety glass, three wipers, electrical adjustable mirrors, electrically operated door window lifters, a glove box and an air conditioning system.
<b>Electrical system</b>	24 V DC, two sets of 12 V battery in series. Generator: 28 V-70 A.
<b>Power battery</b>	Rated capacity: 228 Ah Rated energy: 140.95 kwh Rated voltage: 618.24 V Charge-discharge rate: 1C  Rated capacity: 173 Ah Rated energy: 90.2 kwh Rated voltage: 521.64V Charge-discharge rate: 1C

## 技术规格

### Technical specifications

 Superstructure	
<b>Frame</b>	Designed and manufactured by XCMG, made of high strength steel.
<b>Hydraulic system</b>	Variable pump driven by chassis engine, used for hoisting, elevating and telescoping operations. Load sensing proportional multi-way change valve with impact resistance valve and cavitation-proof valve integrated; air-cooled hydraulic oil radiator.
<b>Control system</b>	Pilot hydraulic control is used for controlling the superstructure. All crane movements are controlled by the hydraulic pump and proportional valve through two control levers on the left and right sides.
<b>Main winch</b>	Hydraulic control is used for speed regulation. The system is driven by a hydraulic motor through a planetary gear reducer, with a normally closed brake, a balanced valve and a Lebus-type grooved drum equipped.
<b>Auxiliary winch</b>	Hydraulic control is used for speed regulation. The system is driven by a hydraulic motor through a planetary gear reducer, with a normally closed brake, a balanced valve and a Lebus-type grooved drum equipped.
<b>Slewing system</b>	Four-point contact-ball slewing ring is driven by the planetary gear reducer of slewing mechanism, which is driven by a hydraulic motor, and may continuously slew 360°. Power control and free slewing function as well as stepless speed regulation are available. There is a horn switch fitted on the slewing control lever.
<b>Luffing system</b>	A front support double-acting hydraulic cylinder is equipped for luffing operation, with a balance valve fitted.
<b>Operator's cab</b>	New steel cab with a full-view windshield, safety glass, sun shield and adjustable operator's seat. Windshield wiper and roof window wiper are fitted. Crane control levers are integrated into armrests. A sliding door and a pull-out step are designed for easy and safe access to the cab. Heater and air conditioner are equipped as a standard.
<b>Safety devices</b>	Hydraulic balance valve, hydraulic relief valve, double-way hydraulic valve, LMI, lowering limiter for preventing wire rope from over-releasing, anti-two block at boom head for preventing wire rope from over-winding and tri colored light bar.

 Boom system	
<b>Boom</b>	5-section boom with U-shaped cross-section, welded structure. Double-cylinder plus ropes telescoping system Boom length: 11.2 m~44 m.
<b>Single top</b>	Fitted at boom head, used for single line operation. Its lifting performance is the same as that for boom, but the maximum lifting load does not exceed 3 t.
<b>Fixed jib</b>	One-section lattice jib, welded structure. Three offset angles of 0°, 15° and 30° . Fixed jib length: 9 m.

## 车型与选装件

### Version and optional equipment

车型 Version	功能描述 Function description	选择 Selection
标准型 Standard	五节主臂44m, 固定副臂9m 5-section boom of 44 m, fixed jib of 9 m	

注释: 该产品仅标准型一种车型。

Note: only standard version is available for this model.

可选装件 Optional equipment		选择 Selection
回转报警装置 Warning device for slewing		



## 重量 Weight



车桥 Axle	1	2	3	总重量 Total weight
t	9	13	13	35

携带：副臂、副卷、主钩

Carried with: jib, auxiliary winch, main hook block

拆除：3吨副钩，臂端单滑轮、备胎和备胎支架、支脚盘




Removed: 3 t auxiliary hook block, single top, spare tire, spare tire bracket, outrigger floats








吊钩 Hook block	倍率 Parts of line	吊钩重量 Weight (kg)	吊钩尺寸 Dimensions (mm)	备注 Remarks
25t	8	260	366×430×1252	单钩 Single hook
3t	1	60	236×236×503	单钩 Single hook

## 作业速度 Working speeds




		
315/80 R 22.5	2.5 ~ 85	60%



作业机构 Operation mechanisms	作业速度 Working speed	最大单绳拉力 Max. single line pull	钢丝绳直径/长度 Rope diameter/ length
	0-135 m/min, 单绳, 第四层 m/min, single line, 4th layer	30 kN	16 mm/185m
	0-135 m/min, 单绳, 第四层 m/min, single line, 4th layer	30 kN	16 mm/110 m
	0-2.0 r/min		
	从-2°抬起至79°约35s Approx. 35 s for boom luffing from -2° to 79°		
	从11.2m伸出至44m约100s Approx. 100s for boom extending from 11.2 m to 44 m		


## 臂架组合方案

### Boom / Jib combinations




主臂  
Telescopic boom

T: 11.2~44m



副臂  
Jib






T: 11.2~44m  
J: 9 m



# 起重性能表

## Lifting capacities







T 11.2~44.0m


	 11.2-44.0m	 5.6m×6.4m	 360°					
	11.2m	15.4m	19.5m	25.6m	31.7m	37.9m	44m	
3	25000	25000						3
3.5	25000	25000						3.5
4	25000	25000	21000					4
4.5	25000	24500	20500					4.5
5	24600	24000	20000	18700				5
5.5	23000	21500	19800	18700				5.5
6	20800	20000	19500	17800				6
6.5	19600	19500	18200	16800	13800			6.5
7	17800	18000	16500	16000	13800			7
8	14400	14000	13800	14500	13000	9800		8
9		11200	11000	11800	12300	9800		9
10		9200	9000	9800	10300	9300	6600	10
11		7700	7500	8200	8700	9000	6400	11
12			6200	7000	7400	7700	6200	12
13			5300	6000	6400	6700	6100	13
14			4400	5100	5600	5800	5900	14
15			3800	4500	4900	5100	5300	15
16				3850	4300	4500	4700	16
18				2900	3300	3600	3800	18
20				2100	2500	2800	3000	20
22					1900	2200	2400	22
24					1400	1700	1900	24
26					1000	1300	1500	26
28						950	1150	28
30						650	850	30
32							600	32

# 起重性能表

## Lifting capacities

T 17.4~39.9m








									
	17.4m	23.6m	29.7m	35.8m	21.5m	27.7m	33.8m	39.9m	
3	24000								3
3.5	24000								3.5
4	24000				21000				4
4.5	23000	21000			21000				4.5
5	22000	21000			21000				5
5.5	20000	21000			21000	17500			5.5
6	19600	21000	11800		21000	17500			6
6.5	18800	21000	11800		21000	17500			6.5
7	17600	20000	11800		19100	17500	10800		7
8	15500	16000	11300	8500	15000	15500	10800		8
9	12600	13100	10600	8200	12100	12600	10800		9
10	10500	11000	9700	7900	10100	10600	10100	7400	10
11	8900	9300	9000	7300	8500	9000	9200	7100	11
12	7700	8100	8300	6900	7300	7700	8000	6800	12
13		7100	7300	6700	6200	6700	7000	6600	13
14		6200	6400	6400	5400	5800	6100	6100	14
15		5500	5700	5800	4700	5100	5400	5500	15
16		4900	5100	5300	4100	4500	4800	4900	16
18		3900	4100	4300		3600	3800	3900	18
20			3400	3500		2800	3000	3200	20
22			2700	2900		2200	2400	2600	22
24			2200	2400			1900	2100	24
26				2000			1500	1700	26
28				1600				1350	28
30								1050	30
32								800	32



# 起重性能表

## Lifting capacities

T 44.0m

	    				
	0°	15°	30°		
78	3000	2800	2100	78	
75	3000	2500	1900	75	
72	2900	2300	1800	72	
70	2700	2250	1700	70	
65	2200	2000	1600	65	
60	1400	1300	1200	60	
55	900	800	800	55	
50	500	500	500	50	

# 主要技术参数表

## Table of main technical parameters

类别 Category	项目 Item	单位 Unit	参数 Parameter	
尺寸参数 Dimensions	外形尺寸 (长×宽×高) Dimensions (length×width×height)	mm	13485×2550×3470	
	轴距 Wheel base	mm	4900+1350	
	轮距 (前/后) Track (Front/ Rear )	mm	2118/1838	
	前悬/后悬 Front/ Rear overhang	mm	2475/2256	
	前伸/后伸 Front/ Rear extension	mm	1770/734	
重量参数 Weight	最大允许总质量 Max. permissible total weight	kg	35000	
	轴荷 Axle load	一轴 1st axle	kg	9000
		二轴 2nd axle	kg	13000
		三轴 3rd axle	kg	13000
动力参数 Power	发动机型号 Engine model	—	SC7H270Q6	
	额定功率/转速 Rated power/rpm	kW/(r/min)	199kw(2300r/min)	
	最大净功率/转速 Max. net power/rpm	kW/(r/min)	197kw(2300r/min)	
	最大扭矩/转速 Max. torque/rpm	N.m/(r/min)	1000N.m (1200-1700r/min)	
行驶参数 Travel	最高车速 Max. travel speed	km/h	≥85	
	最低稳定车速 Min. stable travel speed	km/h	2.5~3	
	最小转弯直径 Min. turning diameter	m	≤22	
	臂头最小转弯直径 Min. turning diameter at boom tip	m	≤26.95	
	最小离地间隙 Min. ground clearance	mm	230	
	接近角 Approach angle	°	11	
	离去角 Departure angle	°	13	
	制动距离(制动初速度为30km/h) Braking distance (at 30 km/h )	m	≤10	
	最大爬坡能力 Max. grade ability	%	≥60	
	百公里油耗 Fuel consumption per 100 km	L	25	
噪音 Noise	加速行驶机外噪声 Exterior noise level	dB(A)	≤84	
	驾驶员耳旁噪声 Noise level at seated position	dB(A)	≤80	



# 主要技术参数表

## Table of main technical parameters

类别 Category	项目 Item		单位 Unit	参数 Parameter	
主要性能参数 Main performance	最大额定总起重量 Max. total rated lifting capacity		t	25	
	最小额定工作幅度 Min. rated working radius		m	3	
	转台尾部回转半径 Turning radius at turntable tail	平衡重处 Counterweight	mm	3800	
		副卷处 Auxiliary winch	mm	—	
	最大起重力矩 Max. load moment	基本臂 Base boom	kN.m	1249	
		最长主臂 Fully-extended boom	kN.m	809	
		最长主臂+副臂 Fully-extended boom + Jib	kN.m	513	
	支腿跨距 Outrigger span	纵向 Longitudinal	m	5.6	
		横向 Lateral	m	6.4	
	起升高度 Hoist height	基本臂 Base boom	m	11.5	
		最长主臂 Fully-extended boom	m	43.8	
		最长主臂+副臂 Fully-extended boom + Jib	m	52	
	起重臂长度 Boom length	基本臂 Base boom	m	11.2	
		最长主臂 Fully-extended boom	m	44	
最长主臂+副臂 Fully-extended boom + Jib		m	53		
副臂安装角 Jib offset angle		°	0, 15, 30		
工作速度参数 Working speed	起重臂起臂时间 Boom raising time		s	≤35	
	起重臂全伸时间 Boom fully extended time		s	≤100	
	最大回转速度 Max. slewing speed		r/min	≥2.0	
	支腿收放时间 Outrigger extending and retracting time	水平支腿 Outrigger beam	收 Retracting	s	≤20
			放 Extending	s	≤30
		垂直支腿 Outrigger jack	收 Retracting	s	≤25
			放 Extending	s	≤35
起升速度 (单绳,第四层,空载) Hoisting speed (single line, 4th layer, no load)	主起升机构 Main winch		m/min	≥135	
	副起升机构 Auxiliary winch		m/min	≥135	
噪声 Noise	机外辐射 Exterior noise level		dB (A)	≤108	
	司机位置处 Noise level at seated position		dB (A)	≤85	

# 符号标识

## Description of symbols

### 常规标识

#### General symbols

	上车 Superstructure		底盘 Chassis
	起重能力 Lifting capacity		车桥 Axle
	吊臂长度 Boom length		行驶速度 Driving speed
	工作幅度 Radius		爬坡能力 Grade ability
	吊臂仰角 Boom angle		轮胎 Tires
	主臂起升高度 Hoist height with boom		支腿 Outriggers
	固定副臂长度 Fixed jib length		吊钩 Hook block
	副臂安装角 Jib offset angle		卷扬 Winch
	副臂起升高度 Hoist height with jib		使用第五支腿360°全回转 360° operation of the boom with 5th jack
			不使用第五支腿侧后方作业 Without 5th jack, boom over side and over rear

# 注意事项

## Notes

1. 表中额定总起重量值，是在平整的坚固地面上本起重机能够保证的最大总起重量，包括吊钩和吊具的重量，所以为了估算重物重量，必须减去上述的装置重量。
2. 表中的工作幅度为起吊重物离地时起重物到起重机回转轴线的水平距离，是包括起重臂变形量在内的实际值，因而起吊前应考虑起重臂变形量。
3. 只允许在5级(瞬时风速14.1m/s，风压125N/m<sup>2</sup>)风以下进行作业。
4. 吊重前操作者必须对物体的重量和工作范围了解后选择合适的作业工况，严禁超出表中的数值。幅度及臂长在相邻两个数值之间时，应依据两个数值中较小值确定起重作业。
5. 应按主臂仰角范围作业，即使是空载，也不应使主臂仰角处于范围外，谨防整机倾翻。
6. 表中的主臂长度应要按照每节臂的伸缩要求进行伸出。
7. 本手册仅供参考，所有信息均仅供说明，不应依赖它去操作起重机，起重机的正确操作说明请参见操作手册和额定起重量手册

1. The total rated loads given in the rated load charts are the maximum lifting capacity when the crane is set up on firm and level ground, which includes the weight of the hook block and slings. The weight of above-mentioned devices should be deducted to correctly calculate the load weight.
2. The working radius shown in the rated load charts is the radius when the load is lifted off the ground, and it is the actual value including loaded boom deflection.
3. A lifting operation is permissible only when the wind force is below grade 5 (instantaneous wind speed is 14.1 m/s, wind pressure is 125 N/m<sup>2</sup>).
4. Before beginning lifting operation, the operator should know the weight of the load to be lifted and its working range, and then select proper working conditions. Never operate the crane beyond the limit shown in the chart. Use the lower value from the chart when the boom length or working radius is between the range of values.
5. Observe the boom angle limit. Never operate the crane with the boom angle beyond the recommended limit even if a load is not being carried. Otherwise, the crane will tip.
6. The boom length given in the rated load charts should accord with the telescoping code of boom sections .
7. The manual is intended as reference only. See Operation Manual and Rated Lifting Capacity Manual for correct operation instructions.



**地址:** 江苏省徐州市经济技术开发区高新路68号  
**Add:** No. 68 Gaoxin Road,  
Economic and Technological Development Zone,  
Xuzhou, Jiangsu, China  
**电话(Tel):** +86-516-83462242/83462350  
**质量监督电话(Quality Inquiry Tel):** +86-516-  
87888268  
**备件电话(Spare Parts Tel):** +86-516-83461542  
**邮编(Post Code):** 221004  
**网址(Web):** www.xcmg.com/qizhongji

**服务热线 Service Tel**

**400-110-9999**

**400-001-5678**



本印刷品不属于合同。出于产品不断改进的需要，我们保留对产品型号、参数、配置进行变更的权利，恕不另行通知。图片仅供参考，具体产品以实物为准。图片中产品可能并非标准配置，部分部件可能需要另行购置。办理牌照和上路行驶需遵守当地法规。

This print does not belong to the contract. We reserve the right to modify the design (such as product model, parameters and configuration) without notice for improvement. The pictures are just for reference. The product in the picture may not be standard configuration. Some parts need to be purchased separately. Conform to the local laws for license application and road traveling.